

Solutions for Rotational Molding

- External Mold Release
- Internal Mold Release
- Cleaners & Mold Strippers



External Mold Releases

		Product No.	Primary Use	Features/Benefits	Application
XTEND®	Water-based	W-4008	All PE, PP, & PA	High-performance, long lasting semi-permanent release provides quick and easy demolds, and the highest number of demolds prior to needing reapplication. Provides excellent cosmetics, and minimal build-up.	Wipe or spray on ambient to warm molds. Mold up to 1000°F/528°C. No baking required.
		W-4016	XLPE	Medium to high slip, semi-permanent designed for cross-linked polyethylene. Also works for all grades of PE.	Wipe or spray on ambient to warm molds. No baking required.
	Solvent-based	19RSS	LDPE, LLDPE, MDPE, HDPE, PP	Quick, easy-to-apply, semi-permanent release; often preferred for short runs or cast iron molds. High slip for difficult to release parts.	Wipe or spray on ambient to warm molds.
MoldWiz®	Water-based	WB-4606	XLPE	Low to medium slip. Excellent for eliminating coining and pock-marking. Can also be used as a general purpose release for other PE grades.	Wipe or spray on ambient to warm molds. No baking required.
		WB-4707	Parting lines, pins, inserts, cores	Very high-slip for parting lines. Keeps parting lines clean and free of resin. Also excellent for pins, cores, inserts, etc.	Wipe on or dip at ambient to warm.

Internal Mold Release

		Product No.	Primary Use	Features/Benefits	Application
MoldWiz®	Powder	INT-33LCA	All types of PE & PP	Imparts excellent release for difficult parts as well as providing improved flow and anti-static properties. Does not impair mold in graphics, post-applied labels, etc.	Typical addition rate is .05% - .1% of the weight of the resin. May be dry blended, although addition prior to grinding or compounding can be done.

Cleaners

		Product No.	Primary Use	Features/Benefits	Application
CleanWiz®	Water-based	WCX	Cleaning all types of molds	100% water-based stripper for removing light mold build-up or color plate-out.	Scrub ambient molds & allow to soak for 5-15 mins, scrub with abrasive pad to remove build-up, then rinse with water and dry.
	Solvent-based	CX-200HS	Cleans most tools	Removes build-up of mold release and plate-out of color and resin. For light to moderate build-up.	Scrub ambient molds & allow to soak for 5-15 mins, scrub with abrasive pad to remove build-up, then rinse with water and dry.

These products reflect only a small portion of what we have to offer. Please contact us for more information. This information is supplied for technically skilled professionals working at their own risk. AXEL believes the information to be accurate, although the Company assumes no liability in the validity of the information for any specific process or application. Moreover, AXEL will assume no liability from any direct and/or consequential damages of any kind that may occur from the use or non-use of AXEL products or information supplied by the Company or its appointed representatives. ISO 9001 Registered. REACH Compliant. MoldWiz®, XTEND®, PasteWiz® and CleanWiz® are registered trademarks of Axel Plastics Research Laboratories Inc. ©2016 Axel Plastics Research Laboratories, Inc. All rights reserved.

AXEL



For technical data sheets or free samples contact:

Axel Plastics Research Laboratories, Inc.
50 Cambridge Drive
Monroe, CT 06468 USA
1-800-332-AXEL(2935) in USA & Canada
1-203-590-2000
Fax: 1-718-565-7447
www.axelplastics.com
info@axelplastics.com