

technical data



Tel: 718-672-8300 • Fax: 718-565-7447
E-mail: info@axelplastics.com

MOLD WIZ WB-411

General: A liquid external release agent that dries at room temperature forming a mono-molecular film which adheres by absorption to the mold walls and has no affinity for the resin. This selective adhesion prevents the film from easily being torn off by the demolded part. Will not interfere with any secondary operations such as decorating, bonding, or painting.

Use: All types of Polyurethane

Composition: Proprietary emulsion of hydrocarbon and ester wax, organic fatty acids with siloxane based polymer in combination with wetting agents and surfactant in a water vehicle.

TYPICAL PROPERTIES:

SOLIDS:	9.5 – 10.5%
COLOR:	White/Cream Yellow
SPECIFIC GRAVITY:	0.980 @ 25°C
VISCOSITY:	< 50 cps @ 25°C
pH:	9.0 – 11.0
FLASH POINT:	Non Flammable
SHELF LIFE:	Minimum of one year

Application Instructions:

Clean mold with CLEAN WIZ. Spray a heavy coat to break-in the mold. Let it dry. Spray a thin coat (fine mist to dry film) and allow to dry completely with no moisture residue. Accelerate drying time by blowing hot air or by using heat lamps if necessary. Repeat whenever mold has been cleaned or as required to give mold release properties.

All information given by us about our products is based upon our tests and experience. It is intended for use by persons having technical skill at their own discretion and risk, and we assume no liability in connection with their use.

(061121)