

technical data



Address: 50 Cambridge Drive
Monroe, Connecticut
Tel: 203 590-2000 FAX 718 567-7447
E-mail: info@axelplastics.com

MOLD WIZ

AMP-70A Concentrate

General: A liquid external release agent concentrate for wood applications, such as: OSB, MDF, and particleboard.
Will not interfere with any secondary operations, such as: laminating, bonding, or painting.

Use: MDF and Particle Board, UF and MUF resin. Phenolic and Melamine resin based Laminates. Wood veneer adhesives.

Composition: Proprietary synergistic blend of organic acids and esters with wetting agents, surfactants and emulsifiers in a water vehicle.

TYPICAL PROPERTIES:

SOLIDS:	64 – 66%
COLOR:	Cloudy Yellow
SPECIFIC GRAVITY:	0.99 @ 5°C
VISCOSITY:	Soft paste @25°C
pH:	5– 7
FLASH POINT:	Non Flammable
SHELF LIFE:	Minimum of one year

Application Instructions:

Diluting Instructions: Dilute AMP-70A concentrate to a range of 0,5 to 2,0% solids level. Please note that the AMP-70A averages 65% solids. Warm water is recommended for easily miscibility.

All information given by us about our products is based upon our tests and experience. It is intended for use by persons having technical skill at their own discretion and risk, and we assume no liability in connection with their use.

(Jan 29, 2018)