

technical data



PLASTICS RESEARCH LABORATORIES, INC.
MOLD RELEASES & INTERNAL LUBRICANTS

50 Cambridge Drive, Monroe, CT 06468

Tel: 718-672-8300 • Fax: 718-565-7447

E-mail: info@axelplastics.com

MOLD WIZ

AB-25

Anti-Blocking/Moisture Blocking agent

General: A surface active process aid additive, added directly into an aqueous resin system, that imparts moisture resistance (hydrophobicity) to B-staged resin saturated paper. This **anti-blocking** property eliminates undesirable tackiness commonly developed in humid environments and facilitates easy handling and processing. Treated paper may be conveniently stacked, separated and handled as required.

Use: Phenolic, Melamime, Urea Resin

Composition: Proprietary emulsified product of organic fatty acids, esters and amine with wetting agents and surfactants in a water vehicle.

TYPICAL PROPERTIES:

NON-VOLATILES:	14%
COLOR:	Off White
SPECIFIC GRAVITY:	0.990 @ 25°C
VISCOSITY:	<100 cps @ 25°C
pH:	8.7 – 10.7
FLASH POINT:	Non Flammable
SHELF LIFE:	Minimum of one year

Application Instructions:

General: For best results, laboratory tests or pre-production trials should determine the optimum addition level.

All information given by us about our products is based upon our tests and experience. It is intended for use by persons having technical skill at their own discretion and risk, and we assume no liability in connection with their use.

(013014)