

## technical data



50 Cambridge Drive, Monroe, CT 06468

Tel: 718-672-8300 • Fax: 718-565-7447

E-mail: [info@axelplastics.com](mailto:info@axelplastics.com)

# MOLD WIZ INT-LM34

## WETTING AGENT

---

**General:** A wetting agent and flow additive for aqueous resin systems used for saturating papers in the decorative laminate industry. The additive imparts excellent wetting properties and lowers the surface tension value resulting in improved surface quality of decorative laminates.

**Use:** Melamine, Urea and Phenolic water and water/alcohol-based resin systems.

**Composition:** Proprietary emulsified product of organic fatty acids and esters with wetting agents and surfactants in a water/alcohol vehicle.

### TYPICAL PROPERTIES:

<b>NON-VOLATILES:</b>	<b>35%</b>
<b>COLOR:</b>	<b>Water Clear</b>
<b>SPECIFIC GRAVITY:</b>	<b>1.015 @ 25°C</b>
<b>VISCOSITY:</b>	<b>&lt; 150 cps @ 25°C</b>
<b>pH:</b>	<b>8.5</b>
<b>FLASH POINT:</b>	<b>Non Flammable</b>
<b>SHELF LIFE:</b>	<b>Minimum of one year</b>

### Application Instructions:

**General:** For best results, laboratory tests or pre-production trials should determine the optimum addition level. Add Mold Wiz LM-34 to resin solution at room temperature as a last mixing step. Use 2-5g/kg resin solids.

All information given by us about our products is based upon our tests and experience. It is intended for use by persons having technical skill at their own discretion and risk, and we assume no liability in connection with their use.

(060817)