

technical data



PLASTICS RESEARCH LABORATORIES, INC.
MOLD RELEASES & INTERNAL LUBRICANTS

50 Cambridge Drive, Monroe, CT 06468

Tel: 718-672-8300 • Fax: 718-565-7447

E-mail: info@axelplastics.com

MOLD WIZ INT- RW40

General: A process aid additive with surfactant properties, which is added directly to the aqueous solution. The addition of this process aid additive gives the resin improved wetting properties of the paper or substrate being impregnated, reducing or eliminating voids and dry spots. The process aid additive will not interfere with adhesion properties between paper laminates. It will function as an excellent release agent causing the laminate to release easily and cleanly from the caul plate without leaving any residue. This product contains no silicone, no wax and no metallic stearates.

Use: Release agent for water-based resin systems.

NOTE: Do not store this product below 65°F/18°C.

Composition: Proprietary synergistic blend of alkoxyated alcohols glycol ethers.

TYPICAL PROPERTIES:

EFFECTIVE INGREDIENTS:	50%
SOLIDS:	50%
COLOR GARDNER:	Light amber
SPECIFIC GRAVITY:	0.988 @25°C
VISCOSITY:	< 100 cps @25°C
pH:	9.2
FLASH POINT:	Non-Flammable
SHELF LIFE:	One year in original container and packaging

Application Instructions:

General: For best results, laboratory tests or pre-production trials should determine the optimum addition level. Use 0.5-2.0% additive based on solids of process aid additive to solids of resin solution.

Caution: Contents may settle. Mix or Stir well before use.

All information given by us about our products is based upon our tests and experience. It is intended for use by persons having technical skill at their own discretion and risk, and we assume no liability in connection with their use.

(120809)